BEST AVAILABLE COPY   Attorney Docket: 012.P10010

AMENDMENT

IN THE CLAIMS

This listing of claims will replace all prior versions and listings of claims in the application.

Where claims have been amended and/or canceled, such amendments and/or cancellations

are done without prejudice and/or waiver and/or disclaimer, and Assignee reserves the right to

claim this subject matter in a continuing application:

1.   (Currently Amended) A method, comprising:

generating an oscillating electronic signal;

storing in a memory a first phasor associated with [[an]] said electronic signal and a

second phasor generated by multiplying together the first phasor with a delta phasor

associated with a cyclic rate of the electronic signal, the first phasor having a first real portion

and a first imaginary portion, the second phasor having a second real portion and a second

imaginary portion;

storing in the memory a first sum generated by adding the first imaginary portion to

the first real portion;

generating an imaginary correction factor by scaling the first sum according to a first

scaling factor;

correcting a magnitude error of the second phasor by adding the imaginary correction

factor to the second imaginary portion of the second phasor; and

updating the electronic signal based, at least in part, on the corrected second phasor.

2

BEST AVAILABLE COPY   Attorney Docket: 012.P10010

2.   (Previously Presented) The method of claim 1, further comprising:

storing in the memory a first difference generated by subtracting the first imaginary

portion from the first real portion;

scaling the first difference according to the first scaling factor to produce a real

correction factor; and

further correcting the magnitude error of the second phasor by adding the real

correction factor to the second real portion of the second phasor.

3.   (Previously Presented) The method of claim 1, wherein the first scaling factor is

based on a bit-precision of N bits, where N is a non-zero integer.

4.   (Previously Presented) The method of claim 3, wherein the first scaling factor is

further based on a second scaling factor, the second scaling factor being based on a first term

of a Taylor series relating to a square-root.

5.   (Previously Presented) The method of claim 4, wherein the second scaling factor is

based on the formula:

$$\alpha = \left(\frac{1.0 - \left(\cos^2(\omega) + \sin^2(\omega) \right)}{2} \right)$$

where α is the second scaling factor and ω is the frequency of the complex sinusoid.

6.   (Previously Presented) The method of claim 5, wherein the second scaling factor is

determined according to the formula $\alpha \approx 2^{-P}$, where P is a non-zero integer.

3

BEST AVAILABLE COPY

7.   (Previously Presented) The method of claim 6, wherein the first scaling factor is equal to $2^{-(P+N)}$.

8.   (Previously Presented) The method of claim 7, wherein the step of scaling is performed using a shift operation.

9.   (Previously Presented) The method of claim 1, wherein the step of scaling is performed using a shift operation.

10.   (Previously Presented) The method of claim 1, further comprising updating the electronic signal based on a third phasor produced a high-accuracy technique.

11.   (Previously Presented) The method of claim 1, wherein the electronic signal is an electronic analog signal having sinusoidal form.

12.   (Previously Presented) The method of claim 1, further comprising producing a communication signal based on the updated electronic signal.

13.   (Previously Presented) The method of claim 1, further comprising receiving a communication signal using the updated electronic signal.

14.   (Previously Presented) The method of claim 2, wherein the steps of scaling are performed using a shift operation of N+P bits, where N is a target bit-precision and P is a non-zero integer such that

4

BEST AVAILABLE COPY

$$2^{-P} \approx \left(\frac{1.0 - \left(\cos^2(\omega) + \sin^2(\omega) \right)}{2} \right)$$

where ω is the frequency of the complex sinusoid.

15.   (Previously Presented) An apparatus for producing an electronic signal, comprising:

a multiplier that multiplies a first phasor associated with the electronic signal and a delta phasor associated with a cyclic rate of the electronic signal to produce a second phasor, the first phasor having a first real portion and a first imaginary portion, the second phasor having a second real portion and a second imaginary portion;

an arithmetic device that adds the first imaginary portion to the first real portion to produce a first sum;

a scaling device that scales the first sum according to a first scaling factor to produce an imaginary correction factor;

an adding device that adds the imaginary correction factor to the second imaginary portion of the second phasor to correct for a magnitude error of the second phasor; and

an interface that updates the electronic signal based on the corrected second phasor.

16.   (Previously Presented) The method of claim 15, wherein the electronic signal is an electronic analog signal having sinusoidal form.

17.   (Previously Presented) The method of claim 15, wherein the electronic signal is a communication signal having embedded information.

5

BEST AVAILABLE COPY

18.   (Previously Presented) The apparatus of claim 15, wherein the arithmetic device further subtracts the first imaginary portion from the first real portion to produce a first difference, the scaling device further scales the first difference according to the first scaling factor to produce a real correction factor; and the adding device further adds the real correction factor to the second real portion of the second phasor to further correct for the magnitude error of the second phasor.

19.   (Previously Presented) The apparatus of claim 15, wherein the first scaling factor is based on a bit-precision of N bits, where N is a non-zero integer.

20.   (Previously Presented) The apparatus of claim 15, wherein the first scaling factor is further based on a second scaling factor, the second scaling factor being based on a first term of a Taylor series.

21.   (Previously Presented) The apparatus of claim 16, wherein the second scaling factor is based on the formula:

$$\alpha = \left(\frac{1.0 - \left(\cos^2(\omega) + \sin^2(\omega) \right)}{2} \right)$$

where α is the second scaling factor and ω is the frequency of the complex sinusoid.

22.   (Previously Presented) The apparatus of claim 21, wherein the second scaling factor is determined according to the formula $\alpha = 2^{-P}$, where P is a non-zero integer.

23.   (Previously Presented) The apparatus of claim 22, wherein the scaling device scales the first sum device using a shift operation.

6

BEST AVAILABLE COPY

Attorney Docket: 012.P10010

24.   (Previously Presented) The apparatus of claim 15, wherein the scaling device scales the first sum device using a shift operation.

25.   (Previously Presented) The apparatus of claim 15, wherein the apparatus further updates the electronic signal based on a third phasor, the third phasor being produced a high-accuracy technique.

26.   (currently amended). A machine-readable medium including instructions for producing an <u>oscillating</u> electronic signal, the instructions being arranged to cause a machine to perform the steps of:

multiplying a first phasor associated with the electronic signal and a delta phasor associated with a cyclic rate of the electronic signal to produce a second phasor, the first phasor having a first real portion and a first imaginary portion, the second phasor having a second real portion and a second imaginary portion;

adding the first imaginary portion to the first real portion to produce a first sum;

scaling the first sum according to a first scaling factor to produce an imaginary correction factor;

adding the imaginary correction factor to the second imaginary portion of the second phasor to correct for a magnitude error of the second phasor; and

updating the electronic signal based <u>at least in part,</u> on the corrected second complex sinusoid phasor.

7

BEST AVAILABLE COPY

27.   (Previously Presented) The machine-readable medium of claim 26, further comprising instructions being arranged to cause a machine to perform the steps of:

subtracting the first imaginary portion from the first real portion to produce a first difference;

scaling the first difference according to the first scaling factor to produce a real correction factor; and

adding the real correction factor to the second real portion of the second phasor to further correct for the magnitude error of the second phasor.

28.   (Previously Presented) The machine-readable medium of claim 27, wherein the steps of scaling are performed using a shift operation of N+P bits, where N is a target bit-precision and P is a non-zero integer such that

$$2^{-P} \approx \left(\frac{1.0 - \left(\cos^2(\omega) + \sin^2(\omega) \right)}{2} \right)$$

where ω is the frequency of the complex sinusoid.

29.   (Previously Presented) An apparatus for producing an electronic signal, comprising:

a multiplying means for multiplying a first phasor associated with the electronic signal and a delta phasor associated with a cyclic rate of the electronic signal to produce a second phasor, the first phasor having a first real portion and a first imaginary portion, the second phasor having a second real portion and a second imaginary portion;

an arithmetic means for adding the first imaginary portion to the first real portion to produce a first sum;

a scaling means for scaling the first sum according to a first scaling factor to produce an imaginary correction factor;

8

BEST AVAILABLE COPY

an adding means for adding the imaginary correction factor to the second imaginary portion of the second phasor to correct for a magnitude error of the second phasor;

an interface that updates the electronic signal based on the corrected second phasor.

30.   (Previously Presented) The apparatus of claim 29, wherein the arithmetic means further subtracts the first imaginary portion from the first real portion to produce a first difference, the scaling means further scales the first difference according to the first scaling factor to produce a real correction factor; and the adding means further adds the real correction factor to the second real portion of the second phasor to further correct for the magnitude error of the second phasor.

31.   (Previously Presented) The apparatus of claim 29, wherein the scaling means performs its scaling without using a multiply operation.

32.   (Previously Presented) The apparatus of claim 29, wherein the scaling means performs its scaling using one or more shift operations.

33.   (Previously Presented) The apparatus of claim 29, further comprising a communication-based device that produces a communication signal using the updated electronic signal.

34.   (Previously Presented) The apparatus of claim 29, further comprising a communication-based device that receives a communication signal using the updated electronic signal.

BEST AVAILABLE COPY

Attorney Docket: 012.P10010

35.   (Currently Amended) A method, comprising:

generating an oscillating electronic signal;

multiplying a first phasor associated with [[an]] said electronic signal and a delta phasor

associated with a cyclic rate of the electronic signal to produce a second phasor;

adding a first correction factor to the second phasor to provide a corrected second

phasor; and

updating the electronic signal based at least in part on the corrected second phasor.

36.   (Previously Presented) The method of claim 35, wherein the first phasor comprises

a first real component and a first imaginary component, and the second phasor has a second

real component and a second imaginary component.

37.   (Previously Presented) The method of claim 36, wherein the first correction factor is

substantially formed by adding the first imaginary portion to the first real portion to produce a

first sum, and scaling the first sum according to a first scaling factor to produce the first

correction factor.

38.   (Previously Presented) The method of claim 37, wherein providing a corrected

second phasor further comprises:

adding the first correction factor to the second imaginary portion of the second phasor

to correct for a magnitude error of the second phasor.

10

BEST AVAILABLE COPY

Attorney Docket: 012.P10010

39.   (Previously Presented) The method of claim 37, further comprising:

subtracting the first imaginary portion from the first real portion to produce a first

difference;

scaling the first difference according to the first scaling factor to produce a second

correction factor; and

adding the second correction factor to the second real portion of the second phasor

to further correct for the magnitude error of the second phasor.

40.   (Previously Presented) The method of claim 39, wherein the first scaling factor is

further based on a second scaling factor, the second scaling factor being based on a first term

of a Taylor series relating to a square-root.

41.   (Previously Presented) The method of claim 40, wherein the second scaling factor is

based on the formula:

$$\alpha = \left(\frac{1.0 - \left(\cos^2(\omega) + \sin^2(\omega) \right)}{2} \right)$$

where α is the second scaling factor and ω is the frequency of a complex sinusoid.

42. (Previously Presented) The method of claim 41, wherein the second scaling factor is

determined according to the formula $\alpha \approx 2^{-P}$, where P is a non-zero integer.

43. (Previously Presented) The method of claim 37, wherein the first scaling factor is equal to

$2^{-(P+N)}$.

11

BEST AVAILABLE COPY

44.   (Previously Presented) The method of claim 39, wherein the scaling is performed using a shift operation.

45.   (Previously Presented) The method of claim 35, further comprising updating the electronic signal based, at least in part, on a third phasor.

46.   (Previously Presented) The method of claim 35, further comprising producing a communication signal based on the updated electronic signal.

47.   (Previously Presented) The method of claim 39, wherein the scaling comprises shifting a binary representation of a first sum of N+P bits, where N is a target bit-precision and P is a non-zero integer such that

$$2^{-P} \approx \left(\frac{1.0 - \left(\cos^2(\omega) + \sin^2(\omega) \right)}{2} \right)$$

where ω is the frequency of a complex sinusoid.

48.   (Previously Presented) A system, comprising:

circuitry to combine a first phasor associated with an electronic signal and a delta phasor associated with a cyclic rate of the electronic signal to produce a second phasor;

circuitry to produce a correction factor;

circuitry to add the correction factor to the second phasor to correct for a magnitude error of the second phasor; and

circuitry to update the electronic signal based, at least in part, on the corrected second phasor.

12

BEST AVAILABLE COPY

13

49.   (Previously Presented) The system of claim 48, wherein the first phasor comprises a first real component and a first imaginary component, the second phasor comprises a second real component and a second imaginary component.

50.   (Previously Presented) The system of claim 48, wherein the electronic signal is a communication signal.

51.   (Previously Presented) The system of claim 49, and further comprising circuitry to subtract the first imaginary component from the first real component to produce a first difference;

     scale the first difference according to a first scaling factor to produce a real correction factor; and

     add the real correction factor to the second real portion of the second phasor to correct for the magnitude error of the second phasor.

52.   (Previously Presented) The system of claim 51, wherein the first scaling factor is based, at least in part, on a bit-precision of N bits, where N is a non-zero integer.

53.   (Previously Presented) The system of claim 51, wherein the first scaling factor is further based, at least in part, on a second scaling factor, the second scaling factor being based on a first term of a Taylor series.

13

54.   (Previously Presented) The system of claim 53, wherein the second scaling factor is based at least in part on the formula:

$$\alpha = \left(\frac{1.0 - \left(\cos^2(\omega) + \sin^2(\omega) \right)}{2} \right)$$

BEST AVAILABLE COPY

where α is the second scaling factor and ω is the frequency of the complex sinusoid.

55.   (Previously Presented) The system of claim 53, wherein the second scaling factor is determined according to the formula $\alpha = 2^{-P}$, where P is a non-zero integer.

56.   (Previously Presented) The system of claim 48, and further comprising circuitry to update the electronic signal based at least in part on a third phasor.

57.   (Currently Amended)   An article comprising: a storage medium having stored thereon instructions that if executed by a computing device performs a method as follows:

combining a first phasor associated with an oscillating electronic signal and a delta phasor associated with a cyclic rate of the electronic signal to produce a second phasor;

adding combing a first correction factor [[to]] with the second phasor to provide a corrected second phasor; and

updating the electronic signal based at least in part on the corrected second phasor.

58.   (Previously Presented) The article of claim 57, wherein the first phasor comprises a first real component and a first imaginary component, and the second phasor has a second real component and a second imaginary component.

14

BEST AVAILABLE COPY

59.   (Previously Presented) The method of claim 58, wherein the instructions, if further

executed, produce a correction factor as follows:

adding the first imaginary portion to the first real portion to produce a first sum;

scaling the first sum according to a first scaling factor to produce a first correction

factor;

adding the first correction factor to the second imaginary portion of the second phasor

to correct for a magnitude error of the second phasor.

60.   (Previously Presented) The method of claim 59, wherein the instructions, if further

executed, perform a method comprising:

subtracting the first imaginary portion from the first real portion to produce a first

difference;

scaling the first difference according to the first scaling factor to produce a second

correction factor; and

adding the second correction factor to the second real portion of the second phasor to

further correct for the magnitude error of the second phasor.

61.   (Previously Presented) The article of claim 60, wherein the first scaling factor is

further based on a second scaling factor, the second scaling factor being based on a first term

of a Taylor series relating to a square-root.

62.   (Previously Presented) The article of claim 61, wherein the second scaling factor is

based on the formula:

$$\alpha = \left(\frac{1.0 - \left(\cos^2(\omega) + \sin^2(\omega)\right)}{2} \right)$$

15

BEST AVAILABLE COPY

where α is the second scaling factor and ω is the frequency of a complex sinusoid.

63.   (Previously Presented) The article of claim 61, wherein the second scaling factor is determined according

to the formula $\alpha \approx 2^{-P}$, where P is a non-zero integer.

64.   (Previously Presented) The article of claim 59, wherein the first scaling factor is equal to $2^{-(P+N)}$.

65.   (Previously Presented) The article of claim 59, wherein the scaling is performed using a shift operation of

N+P bits, where N is a target bit-precision and P is a non-zero integer such that

$$2^{-P} \approx \left(\frac{1.0 - \left(\cos^2(\omega) + \sin^2(\omega) \right)}{2} \right)$$

where ω is the frequency of a complex sinusoid.

16